

```

CCCCCCCCCCCCCCCC
CCCCCCCCCCCCCCCC
CCCCCCCCCCCCCCCC
CCC
CCC
CCC
CCC
CCC
CCC
CCC
CCC
CCC
CCC
CCC
CCC
CCC
CCC
CCC
CCC
CCCCCCCCCCCCCCCC
CCCCCCCCCCCCCCCC
CCCCCCCCCCCCCCCC
DDDDDDDDDDDDDDDD
DDDDDDDDDDDDDDDD
DDDDDDDDDDDDDDDD
DDD
DDD
DDD
DDD
DDD
DDD
DDD
DDD
DDD
DDD
DDD
DDD
DDD
DDD
DDD
DDD
DDDDDDDDDDDDDDDD
DDDDDDDDDDDDDDDD
DDDDDDDDDDDDDDDD
UUUU
UUUU
UUUU
UUUU
UUUU
UUUU
UUUU
UUUU
UUUU
UUUU
UUUU
UUUU
UUUU
UUUU
UUUU
UUUU
UUUUUUUUUUUUUUUU
UUUUUUUUUUUUUUUU
UUUUUUUUUUUUUUUU

```

```
MM      MM      AAAAAA      IIIIII      NN      NN
MM      MM      AAAAAA      IIIIII      NN      NN
MMMM    MMMM    AA      AA      II      NN      NN
MMMM    MMMM    AA      AA      II      NN      NN
MM      MM      AA      AA      II      NNNN     NN
MM      MM      AA      AA      II      NNNN     NN
MM      MM      AA      AA      II      NN      NN
MM      MM      AA      AA      II      NN      NN
MM      MM      AAAAAAAAAA      II      NN      NNNN
MM      MM      AAAAAAAAAA      II      NN      NNNN
MM      MM      AA      AA      II      NN      NN
MM      MM      AA      AA      II      NN      NN
MM      MM      AA      AA      IIIIII     NN      NN
MM      MM      AA      AA      IIIIII     NN      NN
```

....
....
....
....

```
LL      IIIIII      SSSSSSSS
LL      IIIIII      SSSSSSSS
LL      II      SS
LL      II      SS
LL      II      SS
LL      II      SS
LL      II      SSSSSS
LL      II      SSSSSS
LL      II      SS
LL      II      SS
LL      II      SS
LL      II      SS
LLLLLLLLLL      IIIIII      SSSSSSSS
LLLLLLLLLL      IIIIII      SSSSSSSS
```

```

1 0001 0 MODULE main          (IDENT='V04-000',
2 0002 0                      MAIN=CDUSMAIN,
3 0003 0                      ADDRESSING_MODE(EXTERNAL=GENERAL))
4 0004 1 = BEGIN
5 0005 1
6 0006 1 *****
7 0007 1 *
8 0008 1 *   COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
9 0009 1 *   DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
10 0010 1 *   ALL RIGHTS RESERVED.
11 0011 1 *
12 0012 1 *   THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
13 0013 1 *   ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
14 0014 1 *   INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
15 0015 1 *   COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
16 0016 1 *   OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
17 0017 1 *   TRANSFERRED.
18 0018 1 *
19 0019 1 *   THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
20 0020 1 *   AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
21 0021 1 *   CORPORATION.
22 0022 1 *
23 0023 1 *   DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
24 0024 1 *   SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
25 0025 1 *
26 0026 1 *****
27 0027 1
28 0028 1
29 0029 1 ++
30 0030 1 Facility:      Command Definition Utility, Main Module
31 0031 1
32 0032 1 Abstract:     This module contains the main routines for the Command
33 0033 1                  Definition Utility, formerly known as the Command Language
34 0034 1                  Editor. The CDU is responsible for maintaining CLI Tables,
35 0035 1                  which are images or object files containing the internal
36 0036 1                  representation of DCL or MCR commands. The primary
37 0037 1                  component of the CDU is a compiler which reads Command
38 0038 1                  Language Definition (CLD) files and compiles them into the
39 0039 1                  internal format. Other features allow the deletion and
40 0040 1                  extraction of information from DCL Tables, plus other
41 0041 1                  goodies.
42 0042 1
43 0043 1                  Special thanks goes to Tim Halvorsen, who wrote the
44 0044 1                  original CDU. It has been rewritten to make it a bit more
45 0045 1                  flexible and easy to maintain, particularly in light of all
46 0046 1                  the enhancements in VMS V4.
47 0047 1
48 0048 1 Environment:  Native, User mode. The following privileges are required:
49 0049 1
50 0050 1                  CMEXEC          For fooling with P1 space.
51 0051 1
52 0052 1 Author:       Paul C. Anagnostopoulos
53 0053 1 Creation:    18 January 1983
54 0054 1
55 0055 1 Modifications:
56 0056 1
57 0057 1

```

MAIN
V04-000

15-Sep-1984 23:43:43
14-Sep-1984 11:58:24

VAX-11 Bliss-32 V4.0-742
DISK\$VMSMASTER:[CDU.SRC]MAIN.B32;1

Page 2
(1)

```
: 58      0058 1  
: 59      0059 1 library 'sys$library:lib';  
: 60      0060 1 require 'cdureq';
```

62	0474	1	!	TABLE OF CONTENTS
63	0475	1	!	-----
64	0476	1		
65	0477	1	forward	routine
66	0478	1		cdu\$main,
67	0479	1		cdu\$delete_mode: novalue,
68	0480	1		cdu\$object_mode: novalue,
69	0481	1		cdu\$replace_mode: novalue,
70	0482	1		cdu\$symbols_mode: novalue,
71	0483	1		cdu\$report_rms_error: novalue;
72	0484	1		
73	0485	1		
74	0486	1	!	EXTERNAL REFERENCES
75	0487	1	!	-----
76	0488	1		
77	0489	1	external	routine
78	0490	1		cdu\$cld,
79	0491	1		cdu\$close_symbol_table_file,
80	0492	1		cdu\$delete_verb_name,
81	0493	1		cdu\$free_all_nodes,
82	0494	1		cdu\$generate_table_blocks,
83	0495	1		cdu\$open_next_cld,
84	0496	1		cdu\$prepare_input_table,
85	0497	1		cdu\$prepare_listing_file,
86	0498	1		cdu\$prepare_new_table,
87	0499	1		cdu\$prepare_object_file,
88	0500	1		cdu\$report_listing_trailer,
89	0501	1		cdu\$write_object_file,
90	0502	1		cdu\$write_output_table,
91	0503	1		cdu\$write_symbol_table_file,
92	0504	1		cli\$get_value,
93	0505	1		cli\$present,
94	0506	1		str\$trim;
95	0507	1		
96	0508	1	external	
97	0509	1		cdu\$gl_cld_errors: long;

MAIN
V04-000

N 2
15-Sep-1984 23:43:43
14-Sep-1984 11:58:24

VAX-11 Bliss-32 V4.0-742
DISK\$VMSMASTER:[CDU.SRC]MAIN.B32;1

Page 4
(3)

```

: 99      0510 1  !      G L O B A L   D A T A
: 100     0511 1  !      -----
: 101     0512 1  !
: 102     0513 1  ! The following item specifies the facility string to be used in object files
: 103     0514 1  ! or any other files we create.
: 104     0515 1
: 105     0516 1 global bind
: 106     0517 1      cdu$facility_string = dtext('VAX/VMS Command Definition Utility (V4-001)'): descriptor;
```

```

: 108      0518 1  :++
: 109      0519 1  :Description: This is the main routine of the Command Definition Utility.
: 110      0520 1  :It is responsible for determining which operating mode the
: 111      0521 1  :user has requested and invoking a routine for that mode.
: 112      0522 1  :
: 113      0523 1  :Parameters: None.
: 114      0524 1  :
: 115      0525 1  :Returns: Most severe status encountered during execution.
: 116      0526 1  :
: 117      0527 1  :Notes:
: 118      0528 1  :--
: 119      0529 1  :
: 120      0530 1  :GLOBAL ROUTINE cdu$main
: 121      0531 2  := BEGIN
: 122      0532 2  :
: 123      0533 2  :own
: 124      0534 2  :    worst_status: long initial(msg(cdu$_success));

```

```

: 126 0535 2 ! The following routine is the global condition handler. Its purpose is to
: 127 0536 2 ! save the worst status that is signalled during the execution of the CDU.
: 128 0537 2 ! It is this status that is returned to DCL.
: 129 0538
: 130 0539 ROUTINE condition_handler(signal_vector: ref vector[,long])
: 131 0540 = BEGIN
: 132 0541
: 133 0542 bind
: 134 0543     status = signal_vector[1]: long;
: 135 0544 own
: 136 0545     severity_map: vector[8,byte] initial(byte(2,0,3,1,4,4,4,4));
: 137 0546
: 138 0547 if .severity_map[.status<0,3,0>] gtru .severity_map[.worst_status<0,3,0>] then
: 139 0548     worst_status = .status;
: 140 0549
: 141 0550 return false;
: 142 0551
: 143 0552 2 END;

```

```

                                .TITLE MAIN
                                .IDENT \V04-000\
                                .PSECT $SPLIT$,NOWRT,NOEXE,2
64 6E 61 6D 6D 6F 43 20 53 4D 56 2F 58 41 56 00000 P.AAB: .ASCII \VAX/VMS Command Definition Utility (V4-0\
69 74 55 20 6E 6F 69 74 69 6E 69 66 65 44 20 0000F
                                30 2D 34 56 28 20 79 74 69 6C 0001E
                                00 29 31 30 0002B
                                010E002B 0002C P.AAA: .ASCII \01)\<0>
                                00000000' 00030 .LONG 17694763
                                .ADDRESS P.AAB
                                .PSECT $OWNS$,NOEXE,2
                                00000000G 00000 WORST_STATUS:
                                04 04 04 04 01 03 00 02 00004 SEVERITY_MAP:
                                .LONG CDUS_SUCCESS
                                .BYTE 2, 0, 3, 1, 4, 4, 4, 4
                                CDUSFACILITY_STRING==
                                P.AAA
                                .EXTRN CDUSCLD, CDUSCLOSE SYMBOL_TABLE_FILE
                                .EXTRN CDUSDELETE VERB NAME
                                .EXTRN CDUSFREE ACL_NODES
                                .EXTRN CDUSGENERATE_TABLE_BLOCKS
                                .EXTRN CDUSOPEN NEXT CLD
                                .EXTRN CDUSPREPARE_INPUT_TABLE
                                .EXTRN CDUSPREPARE_LISTING_FILE
                                .EXTRN CDUSPREPARE_NEW_TABLE
                                .EXTRN CDUSPREPARE_OBJECT_FILE
                                .EXTRN CDUSREPORT LISTING-TRAILER
                                .EXTRN CDUSWRITE_OBJECT_FILE
                                .EXTRN CDUSWRITE_OUTPUT_TABLE
                                .EXTRN CDUSWRITE_SYMBOL_TABLE_FILE
                                .EXTRN CLISGET VALUE, CLISPRESENT
                                .EXTRN STRSTRIM, CDUSGL_CLD_ERRORS
                                .EXTRN CDUS_SUCCESS

```

.PSECT \$CODE\$,NOWRT,2

000C 00000 CONDITION HANDLER:

51	52	04	53	0000'	CF	9E	00002	.WORD	Save R2,R3	:	0539
50	62		AC		04	C1	00007	MOVAB	WORST_STATUS, R3	:	
	63		03		00	EF	0000C	ADDL3	#4, SIGNAL_VECTOR, R2	:	0543
		04	03		00	EF	00011	EXTZV	#0, #3, (R2), R1	:	0547
			03		00	EF	00011	EXTZV	#0, #3, WORST_STATUS, R0	:	
		04	A340	04	A341	91	00016	CMPB	SEVERITY_MAP[R1], SEVERITY_MAP[R0]	:	
					03	1B	0001D	BLEQU	1\$:	
			63		62	D0	0001F	MOVL	(R2), WORST_STATUS	:	0548
					50	D4	00022	CLRL	R0	:	0550
					04	00024	1\$:	RET		:	0552

; Routine Size: 37 bytes, Routine Base: \$CODE\$ + 0000

```

: 145      0553 2 ! Main routine.
: 146      0554 2 ! Establish a global condition handler to save the worst status that is
: 147      0555 2 ! signalled.
: 148      0556 2
: 149      0557 2 enable
: 150      0558 2 condition_handler;
: 151      0559 2
: 152      0560 2 ! Determine which operating mode the user wants. This is specified by a
: 153      0561 2 ! major qualifier on the SET COMMAND command, of which /REPLACE is the default.
: 154      0562 2
: 155      0563 2 if cli$present(dtext('DELETE')) then
: 156      0564 2     cdu$delete_mode()
: 157      0565 2 else if cli$present(dtext('OBJECT')) then
: 158      0566 2     cdu$object_mode()
: 159      0567 2 else if cli$present(dtext('SYMBOLS')) then
: 160      0568 2     cdu$symbols_mode()
: 161      0569 2 else
: 162      0570 2     cdu$replace_mode();
: 163      0571 2
: 164      0572 2 ! Return the worst status that was signalled, with the inhibit flag set.
: 165      0573 2
: 166      0574 2 return .worst_status + sts$m_inhib_msg;
: 167      0575 2
: 168      0576 1 END;
```

.PSECT \$SPLITS,NOWRT,NOEXE,2

```

00 00 45 54 45 4C 45 44 00034 P.AAD: .ASCII \DELETE\<0><0>
                                010E0006 0003C P.AAC: .LONG 17694726
                                00000000 00040 .ADDRESS P.AAD
00 00 54 43 45 4A 42 4F 00044 P.AAF: .ASCII \OBJECT\<0><0>
                                010E0006 0004C P.AAE: .LONG 17694726
                                00000000 00050 .ADDRESS P.AAF
00 53 4C 4F 42 4D 59 53 00054 P.AAH: .ASCII \SYMBOLS\<0>
                                010E0007 0005C P.AAG: .LONG 17694727
                                00000000 00060 .ADDRESS P.AAH
```

.PSECT \$CODE\$,NOWRT,2

```

                                0004 00000 .ENTRY CDUSMAIN, Save R2
52 00000000G 00 9E 00002 MOVAB CLISP$PRESENT, R2
6D 0044 CF DE 00009 MOVAL 5$, (FP)
0000' CF 9F 0000E PUSHAB P.AAC
62 01 FB 00012 CALLS #1, CLISP$PRESENT
07 50 E9 00015 BLBC R0, 1$
0000V CF 00 FB 00018 CALLS #0, CDUSDELETE_MODE
27 11 0001D BRB 4$
0000' CF 9F 0001F 1$: PUSHAB P.AAE
62 01 FB 00023 CALLS #1, CLISP$PRESENT
07 50 E9 00026 BLBC R0, 2$
0000V CF 00 FB 00029 CALLS #0, CDUSOBJECT_MODE
16 11 0002E BRB 4$
0000' CF 9F 00030 2$: PUSHAB P.AAG
```

```

: 0530
: 0531
: 0563
: 0564
: 0565
: 0566
: 0567
```

MAIN
V04-000

F 3
15-Sep-1984 23:43:43
14-Sep-1984 11:58:24

VAX-11 Bliss-32 V4.0-742
DISK\$VMSMASTER:[CDU.SRC]MAIN.B32;1

Page 9
(6)

	62		01	FB	00034	CALLS	#1, CLISPRESNT	
	07		50	E9	00037	BLBC	R0, 3\$	
	CF		00	FB	0003A	CALLS	#0, CDUS\$SYMBOLS_MODE	0568
			05	11	0003F	BRB	4\$	
	0000V	CF	00	FB	00041	CALLS	#0, CDUS\$REPLACE_MODE	0570
50	0000'	CF	8F	C1	00046	ADDL3	#268435456, WORST_STATUS, R0	0574
				04	00050	RET		0576
				0000	00051	WORD	Save nothing	0531
			7E	D4	00053	CLRL	-(SP)	
			5E	DD	00055	PUSHL	SP	
	7E	04	AC	7D	00057	MOVQ	4(AP), -(SP)	
	CF		03	FB	0005B	CALLS	#3, CONDITION_HANDLER	
	FF7B			04	00060	RET		

; Routine Size: 97 bytes, Routine Base: \$CODE\$ + 0025

```

170 0577 1  !++
171 0578 1  ! Description: This routine handles /DELETE mode, in which the user wants
172 0579 1  ! to remove one or more verb names from the CLI table. We
173 0580 1  ! retrieve the list of verb names and delete them from the
174 0581 1  ! table, reporting any errors.
175 0582 1  !
176 0583 1  ! Parameters: None.
177 0584 1  !
178 0585 1  ! Returns: Nothing.
179 0586 1  !
180 0587 1  ! Notes:
181 0588 1  ! --
182 0589 1  !
183 0590 1  GLOBAL ROUTINE cdu$delete_mode : novalue
184 0591 2  = BEGIN
185 0592 2  !
186 0593 2  local
187 0594 2  status: long;
188 0595 2  !
189 0596 2  ! Call a routine to prepare the input CLI table for modification.
190 0597 2  !
191 0598 2  cdu$prepare_input_table();
192 0599 2  !
193 0600 2  ! Loop through the list of verb names to be deleted.
194 0601 2  !
195 0602 2  loop (
196 0603 2  !
197 0604 2  ! We need a buffer with descriptor to get a verb name.
198 0605 2  !
199 0606 2  with_dbuffer(verb_name,32,
200 0607 2  !
201 0608 2  ! Get the next verb name in the list. Quit if there aren't
202 0609 2  ! any more.
203 0610 2  !
204 0611 2  status = cli$get_value(dtext('DELETE'),verb_name);
205 0612 2  if not .status then exitloop;
206 0613 2  str$trim(verb_name,verb_name,verb_name);
207 0614 2  !
208 0615 2  ! Call a routine to delete the verb name from the table.
209 0616 2  !
210 0617 2  status = cdu$delete_verb_name(verb_name);
211 0618 2  check(.status, msg(cdu$_nosuchverb),1,verb_name);
212 0619 2  !
213 0620 2  );
214 0621 2  );
215 0622 2  !
216 0623 2  ! Write out the modified CLI table.
217 0624 2  !
218 0625 2  cdu$write_output_table();
219 0626 2  !
220 0627 2  return;
221 0628 2  !
222 0629 1  END;

```

00	00	45	54	45	4C	45	44	00064	P.AAJ:	.ASCII	\DELETE\<0><0>	:	
						010E0006		0006C	P.AAI:	.LONG	17694726	:	
						00000000		00070		.ADDRESS	P.AAJ	:	
										.EXTRN	CDU\$_NOSUCHVERB	:	
										.PSECT	\$CODE\$,NOWRT,2	:	
										.ENTRY	CDU\$DELETE_MODE, Save R2	:	0590
										SUBL2	#40, SP	:	
										CALLS	#0, CDU\$PREPARE_INPUT_TABLE	:	0599
										MOVL	#32, VERB_NAME	:	0620
										MOVAB	VERB_NAME+8, VERB_NAME+4	:	
										PUSHL	SP	:	
										PUSHAB	P.AAI	:	
										CALLS	#2, CLISGET_VALUE	:	
										MOVL	R0, STATUS	:	
										BLBC	STATUS, 2\$:	
										PUSHL	SP	:	
										PUSHAB	VERB_NAME	:	
										PUSHAB	VERB_NAME	:	
										CALLS	#3, STR\$TRIM	:	
										PUSHL	SP	:	
										CALLS	#1, CDU\$DELETE_VERB_NAME	:	
										MOVL	R0, STATUS	:	
										BLBS	STATUS, 1\$:	
										PUSHL	SP	:	
										PUSHL	#1	:	
										PUSHL	#CDU\$_NOSUCHVERB	:	
										CALLS	#3, LIB\$SIGNAL	:	
										BRB	1\$:	0599
										CALLS	#0, CDU\$WRITE_OUTPUT_TABLE	:	0625
										RET		:	0629

; Routine Size: 96 bytes, Routine Base: \$CODE\$ + 0086


```

: 281      0687 2 cdu$report_listing_trailer();
: 282      0688 2
: 283      0689 2 return;
: 284      0690 2
: 285      0691 1 END;

```

		53 00000000G	00 000C 00000	.ENTRY	CDU\$OBJECT_MODE, Save R2,R3	0643
		50	01 9E 00002	MOVAB	CDU\$GL_CLD_ERRORS, R3	
		00000000G 00	01 90 00009	MOVB	#1, FIRST_CLD	0644
		00000000G 00	00 FB 0000C	CALLS	#0, CDU\$PREPARE_NEW_TABLE	0654
		52	00 FB 00013	CALLS	#0, CDU\$OPEN_NEXT_CLD	0658
			50 D0 0001A	MOVL	R0, CLD_FAB	
			36 13 0001D	BEQL	3\$	0659
			52 DD 0001F	PUSHL	CLD_FAB	0664
		00000000G 00	01 FB 00021	CALLS	#1, CDU\$PREPARE_OBJECT_FILE	
			52 DD 00028	PUSHL	CLD_FAB	0668
		00000000G 00	01 FB 0002A	CALLS	#1, CDU\$PREPARE_LISTING_FILE	
		00000000G 00	00 FB 00031	CALLS	#0, CDU\$CLD	0672
			63 D5 00038	TSTL	CDU\$GL_CLD_ERRORS	0677
			07 12 0003A	BNEQ	1\$	
		00000000G 00	00 FB 0003C	CALLS	#0, CDU\$GENERATE_TABLE_BLOCKS	0678
			63 D5 00043 1\$:	TSTL	CDU\$GL_CLD_ERRORS	0682
			07 12 00045	BNEQ	2\$	
		00000000G 00	00 FB 00047	CALLS	#0, CDU\$WRITE_OBJECT_FILE	0683
		00000000G 00	00 FB 0004E 2\$:	CALLS	#0, CDU\$REPORT_LISTING_TRAILER	0687
			04 00055 3\$:	RET		0691

; Routine Size: 86 bytes, Routine Base: \$CODE\$ + 00E6

```

287 0692 1 1 ++
288 0693 1 1 Description: This routine handles /REPLACE mode, which is the fundamental
289 0694 1 1 mode by which a user adds or replaces command definitions.
290 0695 1 1 We compile a set of CLD files and add/replace the
291 0696 1 1 definitions to an existing CLI table specified by the user.
292 0697 1 1 When compilation is complete, we create a new CLI table
293 0698 1 1 with all the resulting definitions.
294 0699 1 1
295 0700 1 1 Parameters: None.
296 0701 1 1
297 0702 1 1 Returns: Nothing.
298 0703 1 1
299 0704 1 1 Notes:
300 0705 1 1 --
301 0706 1 1
302 0707 1 GLOBAL ROUTINE cdu$replace_mode : novalue
303 0708 2 = BEGIN
304 0709 2
305 0710 2 local
306 0711 2 cld_fab: pointer,
307 0712 2 errors: boolean initial(false);
308 0713 2
309 0714 2
310 0715 2 ! Call a routine to prepare the input CLI table for modification.
311 0716 2
312 0717 2 cdu$prepare_input_table();
313 0718 2
314 0719 2 ! Sit in a loop to compile each CLD file. Open each file in turn, quitting
315 0720 2 ! when we run out of files.
316 0721 2
317 0722 2 while (cld_fab = cdu$open_next_cld()) nequ 0 do (
318 0723 2
319 0724 2 ! Prepare the listing file, if any, to receive the listing.
320 0725 2
321 0726 2 cdu$prepare_listing_file(.cld_fab);
322 0727 2
323 0728 2 ! Parse the CLD file into its intermediate representation.
324 0729 2
325 0730 2 cdu$cld();
326 0731 2
327 0732 2 ! If no syntax errors were discovered, then generate all of the CLI
328 0733 2 ! table blocks from the intermediate representation.
329 0734 2
330 0735 2 if .cdu$gl_cld_errors equ 0 then
331 0736 2 cdu$generate_table_blocks();
332 0737 2
333 0738 2 ! Remember if any errors occurred, so we won't write the new table.
334 0739 2
335 0740 2 if .cdu$gl_cld_errors nequ 0 then
336 0741 2 errors = true;
337 0742 2
338 0743 2 ! Clear away the intermediate representation to prepare for the
339 0744 2 ! next CLD file.
340 0745 2
341 0746 2 cdu$free_all_nodes();
342 0747 2
343 0748 2 ! Finish up the listing file.

```

```

0749      cdu$report_listing_trailer();
0750
0751      );
0752
0753      ! If no errors were discovered, then write out the new CLI table.
0754
0755      if not .errors then
0756          cdu$write_output_table();
0757
0758      return;
0759
0760      END;

```

		001C 00000	.ENTRY	CDU\$REPLACE MODE, Save R2,R3,R4	0707
	54 00000000G	00 9E 00002	MOVAB	CDU\$GL_CLD_ERRORS, R4	
		53 94 00009	CLRB	ERRORS	0708
00000000G	00	00 FB 0000B	CALLS	#0, CDU\$PREPARE_INPUT_TABLE	0717
00000000G	00	00 FB 00012	CALLS	#0, CDU\$OPEN_NEXT_CLD	0722
	52	50 D0 00019	MOVL	R0, CLD_FAB	
		32 13 0001C	BEQL	4\$	
		52 DD 0001E	PUSHL	CLD_FAB	0726
00000000G	00	01 FB 00020	CALLS	#1, CDU\$PREPARE_LISTING_FILE	
00000000G	00	00 FB 00027	CALLS	#0, CDU\$CLD	0730
		64 D5 0002E	TSTL	CDU\$GL_CLD_ERRORS	0735
		07 12 00030	BNEQ	2\$	
00000000G	00	00 FB 00032	CALLS	#0, CDU\$GENERATE_TABLE_BLOCKS	0736
		64 D5 00039	TSTL	CDU\$GL_CLD_ERRORS	0740
		03 13 0003B	BEQL	3\$	
	53	01 90 0003D	MOVB	#1, ERRORS	0741
00000000G	00	00 FB 00040	CALLS	#0, CDU\$FREE_ALL_NODES	0746
00000000G	00	00 FB 00047	CALLS	#0, CDU\$REPORT_LISTING_TRAILER	0750
		C2 11 0004E	BRB	1\$	0722
	07	53 E8 00050	BLBS	ERRORS, 5\$	0755
00000000G	00	00 FB 00053	CALLS	#0, CDU\$WRITE_OUTPUT_TABLE	0756
		04 0005A	RET		0760

; Routine Size: 91 bytes, Routine Base: \$CODE\$ + 013C

```

357 0761 1  |++
358 0762 1  |Description: This routine handles /SYMBOLS mode, in which the user wants to
359 0763 1  |generate a symbol table file from a set of CLD files. The
360 0764 1  |symbol table file is needed when commands make use of the
361 0765 1  |old CLI interface. The symbols define the qualifier and
362 0766 1  |keyword numbers for use with the old CLI callbacks.
363 0767 1  |
364 0768 1  |In this mode, no CLI table blocks are generated.
365 0769 1  |
366 0770 1  |Parameters: None.
367 0771 1  |
368 0772 1  |Returns: Nothing.
369 0773 1  |
370 0774 1  |Notes:
371 0775 1  |--
372 0776 1  |
373 0777 1  GLOBAL ROUTINE cdu$symbols_mode          : novalue
374 0778 2  = BEGIN
375 0779 2  |
376 0780 2  local
377 0781 2  |
378 0782 2  |     symbols_written: boolean initial(false);
379 0783 2  |
380 0784 2  | ! Sit in a loop to compile each CLD file. Open each file in turn, quitting
381 0785 2  | ! when we run out of files.
382 0786 2  |
383 0787 2  while cdu$open_next_cld() neq 0 do (
384 0788 2  |
385 0789 2  |     ! Parse the CLD file into an intermediate representation.
386 0790 2  |
387 0791 2  |     cdu$cld();
388 0792 2  |
389 0793 2  |     ! If no syntax errors were discovered, then add the symbols from
390 0794 2  |     ! this CLD to the symbol table file.
391 0795 2  |
392 0796 2  |     if .cdu$gl_cld_errors eq 0 then (
393 0797 2  |         cdu$write_symbol_table_file();
394 0798 2  |         symbols_written = true;
395 0799 2  |     );
396 0800 2  |
397 0801 2  |     ! Clear away the intermediate representation to prepare for the
398 0802 2  |     ! next CLD file.
399 0803 2  |
400 0804 2  |     cdu$free_all_nodes();
401 0805 2  |
402 0806 2  | );
403 0807 2  | ! Close out the symbol table file if we ever wrote any.
404 0808 2  |
405 0809 2  | if .symbols_written then
406 0810 2  |     cdu$close_symbol_table_file();
407 0811 2  |
408 0812 2  return;
409 0813 2  |
410 0814 1  END;

```

		0004 00000	ENTRY	CDU\$SYMBOLS MODE, Save R2	0777
		52 94 00002	CLRB	SYMBOLS WRITTEN	0778
00000000G	00	00 FB 00004 1\$:	CALLS	#0, CDU\$OPEN_NEXT_CLD	0787
		50 D5 0000B	TSTL	R0	
		22 13 0000D	BEQL	3\$	
00000000G	00	00 FB 0000F	CALLS	#0, CDU\$CLD	0791
	00000000G	00 D5 00016	TSTL	CDU\$GL_CLD_ERRORS	0796
		0A 12 0001C	BNEQ	2\$	
00000000G	00	00 FB 0001E	CALLS	#0, CDU\$WRITE_SYMBOL_TABLE_FILE	0797
	52	01 90 00025	MOVB	#1, SYMBOLS WRITTEN	0798
00000000G	00	00 FB 00028 2\$:	CALLS	#0, CDU\$FREE_ALL_NODES	0804
		D3 11 0002F	BRB	1\$	0787
	07	52 E9 00031 3\$:	BLBC	SYMBOLS WRITTEN, 4\$	0809
00000000G	00	00 FB 00034	CALLS	#0, CDU\$CLOSE_SYMBOL_TABLE_FILE	0810
		04 0003B 4\$:	RET		0814

; Routine Size: 60 bytes, Routine Base: \$CODE\$ + 0197

```
412 0815 1 !++
413 0816 1 Description: This routine is called to report an error from an RMS
414 0817 1 operation.
415 0818 1
416 0819 1 Parameters: message By value, a message status code used for the
417 0820 1 first line of the message. It is assumed
418 0821 1 to take a single !AS $FA0 argument, the file
419 0822 1 spec.
420 0823 1 rms_block By reference, a FAB or RAB which contains
421 0824 1 the error status code.
422 0825 1
423 0826 1 Returns: Nothing.
424 0827 1
425 0828 1 Notes: This routine assumes that all FABs have associated NAM
426 0829 1 blocks.
427 0830 1 --
428 0831 1
429 0832 1 GLOBAL ROUTINE cdu$report_rms_error(message: long,
430 0833 1 rms_block: pointer) : novalue
431 0834 2 = BEGIN
432 0835 2
433 0836 2 local
434 0837 2 fab: pointer,
435 0838 2 nam: pointer,
436 0839 2 file_spec: descriptor;
437 0840 2
438 0841 2
439 0842 2 ! Pick up a pointer to the FAB and NAM blocks.
440 0843 2
441 0844 2 fab = (if .rms_block[fab$b_bid] eglu fab$c_bid then .rms_block else .rms_block[rab$l_fab]);
442 0845 2 nam = .fab[fab$l_nam];
443 0846 2
444 0847 2 ! We need to find a file spec which can be included in the first message
445 0848 2 ! line. Use the one which is most complete.
446 0849 2
447 0850 2 if .nam[nam$b_rsl] nequ 0 then
448 0851 2 build_descriptor(file_spec, .nam[nam$b_rsl], .nam[nam$l_rsa])
449 0852 2 else if .nam[nam$b_esl] nequ 0 then
450 0853 2 build_descriptor(file_spec, .nam[nam$b_esl], .nam[nam$l_esa])
451 0854 2 else
452 0855 2 build_descriptor(file_spec, .fab[fab$b_fns], .fab[fab$l_fna]);
453 0856 2 str$trim(file_spec, file_spec, file_spec);
454 0857 2
455 0858 2 ! Signal the error stored in the RMS block.
456 0859 2
457 0860 2 if .rms_block[fab$b_bid] eglu fab$c_bid then
458 0861 2 signal(.message, 1, file_spec, .rms_block[fab$l_sts], .rms_block[fab$l_stv])
459 0862 2 else
460 0863 2 signal(.message, 1, file_spec, .rms_block[rab$l_sts], .rms_block[rab$l_stv]);
461 0864 2
462 0865 2 return;
463 0866 2
464 0867 1 END;
```

			000C 00000	.ENTRY	CDU\$REPORT_RMS_ERROR, Save R2,R3	: 0832
5E		08	C2 00002	SUBL2	#8, SP	
52	08	AC	D0 00005	MOVL	RMS_BLOCK, R2	: 0844
		53	D4 00009	CLRL	R3	
03		62	91 0000B	CMPB	(R2), #3	
		07	12 0000E	BNEQ	1\$	
		53	D6 00010	INCL	R3	
51		52	D0 00012	MOVL	R2, FAB	
		04	11 00015	BRB	2\$	
51	3C	A2	D0 00017	1\$: MOVL	60(R2), FAB	
50	28	A1	D0 0001B	2\$: MOVL	40(FAB), NAM	: 0845
	03	A0	95 0001F	TSTB	3(NAM)	: 0850
		0E	13 00022	BEQL	3\$	
6E	03	A0	9B 00024	MOVZBW	3(NAM), FILE_SPEC	: 0851
	02	AE	B4 00028	CLRW	FILE_SPEC+2	
04	AE	04	A0 D0 0002B	MOVL	4(NAM), FILE_SPEC+4	
		1F	11 00030	BRB	5\$: 0850
	08	A0	95 00032	3\$: TSTB	11(NAM)	: 0852
		0E	13 00035	BEQL	4\$	
6E	08	A0	9B 00037	MOVZBW	11(NAM), FILE_SPEC	: 0853
	02	AE	B4 0003B	CLRW	FILE_SPEC+2	
04	AE	0C	A0 D0 0003E	MOVL	12(NAM), FILE_SPEC+4	
		0C	11 00043	BRB	5\$: 0852
6E	34	A1	9B 00045	4\$: MOVZBW	52(FAB), FILE_SPEC	: 0855
	02	AE	B4 00049	CLRW	FILE_SPEC+2	
04	AE	2C	A1 D0 0004C	MOVL	44(FAB), FILE_SPEC+4	
		5E	DD 00051	5\$: PUSHL	SP	: 0856
	04	AE	9F 00053	PUSHAB	FILE_SPEC	
	08	AE	9F 00056	PUSHAB	FILE_SPEC	
00000000G 00		03	FB 00059	CALLS	#3, STR\$TRIM	
7E	08	A2	7D 00060	MOVQ	B(R2), -(SP)	: 0863
	08	AE	9F 00064	PUSHAB	FILE_SPEC	
		01	DD 00067	PUSHL	#1	
00000000G 00	04	AC	DD 00069	PUSHL	MESSAGE	
		05	FB 0006C	CALLS	#5, LIB\$SIGNAL	
		04	00073	RET		: 0867

; Routine Size: 116 bytes, Routine Base: \$CODE\$ + 01D3

: 465 0868 1 END
: 466 0869 0 ELUDOM

.EXTRN LIB\$SIGNAL

PSECT SUMMARY

Name	Bytes	Attributes
\$PLITS	116	NOVEC,NOWRT, RD ,NOEXE,NOSHR, LCL, REL, CON,NOPIC,ALIGN(2)
\$OWNS	12	NOVEC, WRT, RD ,NOEXE,NOSHR, LCL, REL, CON,NOPIC,ALIGN(2)
\$CODE\$	583	NOVEC,NOWRT, RD , EXE,NOSHR, LCL, REL, CON,NOPIC,ALIGN(2)

Library Statistics

File	----- Total	Symbols Loaded	----- Percent	Pages Mapped	Processing Time
;\$255\$DUA28:[SYSLIB]LIB.L32;1	18619	19	0	1000	00:01.9

COMMAND QUALIFIERS

BLISS/CHECK=(FIELD,INITIAL,OPTIMIZE)/LIS=LISS:MAIN/OBJ=OBJ\$:MAIN MSRC\$:MAIN/UPDATE=(ENHS:MAIN)

; Size: 583 code + 128 data bytes
; Run Time: 00:14.5
; Elapsed Time: 00:53.0
; Lines/CPU Min: 3608
; Lexemes/CPU-Min: 17373
; Memory Used: 116 pages
; Compilation Complete

0044 AH-BT13A-SE
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION
CONFIDENTIAL AND PROPRIETARY

SYMBOLS LIS
NODES LIS
OBJECT LIS
PARSE1 LIS
PARSE3 LIS
ROUTINES LIS
LISTING LIS
MAIN LIS
TABLE LIS
PARSE2 LIS